TECHNICAL DATA SHEET

PRODUCT CODE: MACIZO

DESCRIPTION: WHITE WB EXTERIOR HI-BUILD 10SH SELF-SEAL

USES: Pigmented waterbase non-yellowing 1k topcoat for spray applications, suitable also as self-sealer, with

good hiding power, superior adhesion properties and chemical resistanct. Formulated for good vertical hang. It has nano-resin technology and contains a UV blocker. It does not contain antifungal agents.

APPLICATION SYSTEM: Desinged for today's various spray application methods.

PRODUCT PREPARATION: Substrate preparation: Raw wood - recommended moisture content is 6-10%. Surface prep by removing

all traces of grease, waxes and resins. Perform sanding with 150 grit paper for softwoods and 180 grit

sandpaper for hardwoods.

Spray application - Ready to Use BlendPartsWBV1038 White WB Exterior Hi-Build 10 Shn S/S100Thinner (water)0-10

FILM THICKNESS: 4-6 mils wet per coat

COATS: Two coats (wet-on-wet application 2-3 hours max)

GENERAL PROPERTIES: Specific Gravity, gr/cc 1.25 +/- 0.05

Viscosity* 30000+/-3000 Solids, % by weight 41 +/- 1

* Brookfield

DRYING TIME:Dust free:35-40 minutes(at 20°C/68°F)Handling:60-70 minutesRH% between 45-65Sandable:12 hoursStackable:24 hours

NOTES: Mix the product before use. The product application on substrate must be done in an environment with

no less than 15°C, (60°F). Coatings applied at lower temperatures will show chemical and mechanical

properties lower than standard performances that can normally be achieved.

SHELF LIFE: 12 Months

Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture

and foreign material. Do not store at temperatures below 7°C (45°F)

DATE OF ISSUANCE: 12-2021